



## CHAIN TRANSFER DEVICE

Systec's Chain Transfer Device (CTD) is a safe and efficient method of moving loads onto and/or off a conveyor line. The features of Systec's CTD allow it to sit within the conveyor line at various locations. It can be moved to nearly any location within the length of the conveyor line. It is totally independent of the conveyor in which it rests and can be added to most other conveyor equipment manufacturer's lines with frame replacement. The CTD is capable of being added to either, Powered Accumulating Roller conveyor (PAR), Powered Roller Only conveyor (PRO), or Gravity Roller Conveyor (GRC).

Additionally, the CTD's chain bars are fully adjustable on a 3" increment to meet any changes in production or configuration requirements. Based on the application, through optional load controls, loads can enter or discharge the device. In certain applications, the device can act as a one, two, three, or four-way intersection. As with all Systec devices, the CTD chain bars are all-welded steel construction, using precision laser cut and machined parts for exact fit and function. This is a low maintenance device applying the most advanced safety designs and features.



### OVERALL CONSTRUCTION

Systec's CTD features a fully guarded chain at all exposed areas. The small diameter, maintenance free sprockets minimize the distance between the feeding conveyor and the CTD itself, limiting load hangup.



### ADJUSTABILITY

Systec's CTD chain bars are adjustable on 3" increments. The device can be installed at various locations within a conveyor line.



### DRIVE ASSEMBLY

Systec's CTD drive is a direct shaft to drive sprocket assembly and tucked neatly into the framework of the device - not chain and sprocket as with most competitors..

# CHAIN TRANSFER DEVICE

## SPECIFICATIONS

Between Frame Dimensions	48", 60", 72", 84", 96"
Lengths	4' - 13' on 1' increments
Top-of-Roller Height	12" T.O.R. (heights over 12" available)
Drive Capacity	3,500 lb/unit
Conveyor Speeds	30, 40 or 60 FPM
Motor Air Requirement	Flange mounted, 3/4 HP, 230/460 Volt, 3-phase, 60 Hertz, standard 80 PSI

## CONSTRUCTION

Chain Bar	Laser cut and welded steel construction
Chain Bar Mounting	Telespar tube, 1" adjustability (3" for rollers)
Chain Guide	Rivet mounted UHMW plastic chain rail
Chain	60# heavy duty chain
Sprocket	13 tooth with precision bearing insert (no bushings)
Shaft	1" diameter idler and drive shaft
Bearing	1" diameter, sealed-for-life, flange mount

## CONTROL OPTIONS

Automatic	Positioning controls with electro-mechanical sensor actuation
Safety Controls	Automatic collision safety
Priority Entry	Automatic load entry from perpendicular conveyor
Manual	Pushbutton operation

