SYSTEC An Alliance. Company

SHEET GRIPPER DEVICE

Systec's Sheet Gripper Device (SGD) is a very simple and effective design that allows deck sheets, or dunnage, to be securely held in place while transferring a load across, onto the held sheets. The feature of Systec's SGD is the wide and angled opening where the deck sheets are placed by the operator. The design lets the operator easily slip single wall, double wall, or multiple sheets into the device. The solid gripper plate, when pneumatically actuated, applies a tremendous force against the sheets assuring a full width, consistent grip. Typical application for the SGD is at the end of a conveyor line, used in conjunction with a Sheet Pusher Device (SPD), Pusher Transfer Device (PTD), or Pop-up Infeed Device (PID) for load transfer onto the deck sheets. The SGD can also be used within a conveyor line for "straight-through" deck sheet loading and conveying. As with all Systec conveyor and devices, the SGD components are all welded steel construction, using precision laser cut parts for exact fit and function. This is a "lowmaintenance" device applying the most advanced designs and features.



OVERALL CONSTRUCTION

Systec's SGD features precision laser cut parts for gripper plate contact and alignment. The main frame of the SGD is all-welded, steel frame construction for long life.



HEAVY DUTY COMPONENTS

Systec's SGD is built using only the best and heaviest gauge of structural and plate steel, making this device virtually indestructible.



ADJUSTABILITY Systec's SGD is factory set on adjustments and therefore, no further adjustments should be required after put into service.

SYSTECCONVEYORS.COM

SHEET GRIPPER DEVICE

SPECIFICATIONS

Device Width	24" to 84" on 1' increments
Device Lengths	2' to 9' on 1' increments
Height	12" T.O.R standard (heights over 12" available)
Load Capacity Air Requirement	3,500 lb/unit

CONSTRUCTION

Frame Gripper Plate Pneumatic Lift Actuators All-welded steel construction 3/8" solid steel, hot rolled plate Firestone #1M1A

CONTROLS

Automatic Manual Photosensor detection Pushbutton operation Foot switch



